

TDS201 Industrial SATA SSD



BIWIN TDS201 SSD uses a high-performance SATA controller, integrating next-generation 4K LDPC error correction, RAID, and SRAM ECC to ensure data integrity and reliability. Tailored for industrial applications and embedded systems, this series is optimized for environments that demand consistent, high-quality data storage and transfer.

Compliant with the SATA III interface standard, the TDS201 SSD features a 2.5" form factor and delivers sequential read and write speeds up to 560 MB/s and 510 MB/s, respectively. With operational temperatures ranging from -20°C to +70°C, it guarantees stable performance in diverse environmental conditions, making it well-suited for critical applications.

Further enhancing data integrity, the TDS201 SSD offers comprehensive features including end-to-end data protection, data inspection, and data erasure, ensuring the integrity of stored information. S.M.A.R.T. monitoring provides real-time visibility into the health of the drive, enabling proactive maintenance through continuous monitoring, diagnostics, and reporting.



Key Features

High-Speed and Stable Performance in Industrial Environments

The BIWIN TDS201 SSD uses high-quality components in its hardware circuitry, ensuring stable performance despite environments ranging from -20°C to +70°C. With sequential read and write speeds up to 560 MB/s and 510 MB/s, it provides high-speed, stable data access capabilities for standard industrial applications.

Multiple Capacities to Meet Diverse Storage Needs

Featuring 3D TLC NAND flash, the BIWIN TDS201 SSD is available in capacities ranging from 32 GB to 2 TB to meet the storage demands of various industries, enabling more efficiency and flexible data management.

Advanced Technologies to Extend Product Lifespan

With features including dynamic/static wear leveling, bad block management, TRIM, and garbage collection, the BIWIN TDS201 SSD ensures optimal utilization of NAND Flash, significantly enhancing the product's durability and lifespan.

Rigorous Industrial Testing for High Reliability

Built to industrial-grade standards, the BIWIN TDS201 SSD undergoes extensive testing, including high and low-temperature performance, functionality tests, and industrial platform compatibility. With an MTBF (Mean Time Between Failures) exceeding 3 million hours, TDS201 offers exceptional reliability.

Flexible Customization to Meet Specialized Requirements

The BIWIN TDS201 SSD offers custom services such as underfill/sidefill, metal/graphene heatsinks, and other tailored options to meet specific customer requirements who need enhanced reliability and durability in specialized environments.

Technologies

S.M.A.R.T.

Firmware Update

End-to-End Data
Protection

Data Erasure

Garbage Collection

Dynamic/Static
Wear Leveling

TRIM Command

Bad Block Management

Intelligent
Thermal Throttling

Applications



Industrial
Automation



Financial and
Retail Device



Self-Service
Terminals



Network
Communications



Smart
Healthcare

Specifications

Model Name	TDS201
Interface	SATA III
Form Factor	2.5" SATA
Flash Type	3D TLC
Firmware	TLC Direct Write
DRAM Cache	DRAM-less
Capacity	32 GB / 64 GB / 128 GB / 256 GB / 512 GB / 1 TB / 2 TB
Sequential Read (Up to)	560 MB/s
Sequential Write (Up to)	510 MB/s
Random Read 4K (Up to)	90K IOPS
Random Write 4K (Up to)	70K IOPS
Read Power Consumption (Max.)	1.33 W
Write Power Consumption (Max.)	2.03 W
Idle Power Consumption (Max.)	0.26 W
Dimensions	100.00 x 69.85 x 6.70 mm
Operating Temperature	-20°C to +70°C
Storage Temperature	-40°C to +85°C
Endurance	3000 P/E cycles
MTBF	>3,000,000 hours
Certifications	CE, FCC, RoHS, HF, REACH
TBW (Up to)	2400 TBW
Warranty	3-Year Limited

Order Information

Capacity	Part Number	Power Loss Protection
32 GB	TD25B03220S0T	Firmware-Based
64 GB	TD25B06420S0T	Firmware-Based
128 GB	TD25B12820S1T	Firmware-Based
256 GB	TD25B25620S1T	Firmware-Based
512 GB	TD25B51220S1T	Firmware-Based
1 TB	TD25B1T220S1T	Firmware-Based
2 TB	TD25B2T220S1T	Firmware-Based

1. Tested by BIWIN labs. Actual performance may vary due to systems, devices, or environment.
2. Maintenance and future updates are required throughout the product lifecycle. Specifications are subject to change without notice.
3. The pictures are for illustration only. Actual products may vary due to product enhancements or changes.
4. Not all products are sold in all regions of the world.
5. As used for storage capacity, one megabyte (MB) = one million bytes, one gigabyte (GB) = one billion bytes, and one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on the operating environment. As used for buffer or cache, one megabyte (MB) = 1,048,576 bytes. As used for transfer rate or interface, megabyte per second (MB/s) = one million bytes per second, and gigabyte per second (GB/s) = one billion bytes per second.
6. MTBF = Mean Time Between Failures based on internal testing using the Telcordia stress testing standard.
7. Please visit www.biwintech.com for warranty details in your region.
8. For more information, please contact sales@biwintech.com.

Global Headquarters:

BIWIN STORAGE TECHNOLOGY CO., LTD.

📍 Building #4, South Zone #2, Zhongguan Honghualing Industrial Zone,
Nanshan District, Shenzhen, Guangdong, China

☎ +86 (755) 2671-5701

✉ sales@biwintech.com



www.biwintech.com